



NOTES:

1. WHEN NATURAL LEADS OF MAGNETICS ARE NOT USED, CHARGER COMPONENTS ARE CONNECTED WITH BLACK FLAME-RETARDANT SWITCHBOARD INSULATION SYSTEM (SIS) TYPE WIRING, IDENTIFIED ON EACH END WITH NUMBER-CODED MARKERS. GROUND WIRES ARE GREEN WITH YELLOW STRIPE.

REV. DRN BY D KJB	CHK BY MCR	APP BY MCR	DATE 12/1/2021	DRN BY KJB	DATE 1/21/2021	<p><b>HINDLEPOWER</b> 1075 Saint John Street Easton, PA 18042-6661 PH 610-330-9000 FAX 610-330-8510 www.hindlepowerinc.com</p>
DESCRIPTION STANDARD DRAWINGS.				CHK BY MCR	DATE 1/21/2021	
ECN NO. N/A				APP BY MCR	DATE 1/21/2021	
PROPERTY AND CONFIDENTIAL NOTICE ANY REPRODUCTION, PARTIAL OR AS A WHOLE OF THIS DOCUMENT WITHOUT THE WRITTEN PERMISSION OF HINDLE POWER, INC IS STRICTLY PROHIBITED.						<p>TITLE <b>ATEVO BATTERY CHARGER CONN DIAGRAM: STYLE 5070 1Ø W/O OPTIONS 6-25A</b></p>
			<p>SCALE <b>B</b> NTS</p>	<p>DWG No <b>JE5255-01</b></p>	<p>REV D</p>	<p>SHEET 1 OF 1</p>